

LED TRI-PROOF LIGHT

T Series Specification sheet



CE   IP66 IK08



PRODUCT DESCRIPTION

Fulton Tri-proof light is usually used in environment which require water-proof ,dust-proof ,corrosion-proof lighting ,such as shopping mall , warehouse and other indoor places . The lamp features with smooth surface , no dust deposition ,can be ceiling mounted or suspending mounted.

FEATURES:







- Water-proof design without adhesive, so there is no water leakage caused by adhesive aging , Convenient to disassemble;
- Light panel and PSU adopt modular design, connected via terminals, easy and convenient to Maintain, no need of soldering;
- Energy saving and eco-friendly, no IR or UV, no mercury contamination , RoHS compliant;
- High transmittance PC cover transmit soft light + small power LEDs, high light efficiency, uniform Light; No dark spot;
- High efficient heat dissipation, LEDs and power supply with low temperature rise, high stability under Continuous working;
- Can be switched on/off frequently, good color rendering performance. Compact appearance, novel design style, easy to install and transport;

APPLICATIONS:

Car Washes/Food processing
 Gas Station/Laboratories
 Industrial Facilities
 Refrigeration/Freezers
 Parking Garage/Utility
 Warehouse/Supermarket
 Chicken farm / Cattle farm



Dimensions(mm)





Technical specifications(Ta=25 °C) GWIT test 650 °C

Model	FLT-TPT-15L6	FLT-TPT-30L12	FLT-TPT-40L15
Length	60 cm (2 feet)	120cm (4 feet)	150cm (5 feet)
Power	15 W	30 W	40 W
Weight	0.4 KG	0.8 KG	1.0 KG
Cover	Diffusion		
Energy Efficiency Class	A+		
Electrical Protection	Class I		
Power supply	Single end/Double end		
Color	3000K / 4000K / 5000K / 6000K		
CRI	>80		
Rated luminous Flux(lm)	1800-1950	3600-3900	4800-5200
Driver	FULTON		
Input Voltage	200~240V AC 50/60Hz		
Power Factor	≥0.92		
THD	≤20%		
Beam angle	120°		
Average Lifespan Ta25°C	>50,000 hours		
Warranty	5 years		
Operating Temperature	-20°C~+45°C		
IP Rating	IP66		
Standard	CE、RoHS、D-MARK、WEEE、IK10		





*Note: 1) 3000K comes up with lower lumen. 2) Luminous Flux tolerance ±5%. 3) The above data are tested by Fulton instruments.

*Please contact your Fulton representative to order products that don't have order codes listed here or any info required




*Due to continuing product improvements, Fulton Lighting reserves the right to change the specifications without notice.

LED Tri-proof light

Photometric Diagram



Lifetime + Sustainability



— Luminous Efficacy - - Rated Luminous Flux - - - CCT — CRI




LED Tri-proof light

Wiring diagram

Cautions:

Before installation, be sure to cut off electricity to avoid electric shock.


This is one end wiring LED Tri-proof light with build-in driver. Powered by the voltage labeled on the LED Tri-proof light , no need to add other drivers.



A hanging



B Ceiling type



LED Tri-proof light

Package Information

Item	Length	O'ty per carton (pcs)	G.W (KG)	Carton size L*W*H (mm)
FLT-TPT-L6	0.6m	20	10.5	690*305*236
FLT-TPT-L12	1.2m	20	18.5	1290*305*236
FLT-TPT-L15	1.5m	20	23	1590*305*236

